



# SINGLEPHASE



**MINIBULL**  
MTF / HEPA14 / WET&DRY  
**SINGLEPHASE**



POWER	Kw	2,4
MAX VACUUM	mBar	250
AIR FLOW	m³ / h	380
VOLTAGE	V	230
MOTORS	n° / Q.ty	2
FILTER MEDIA	IFA / BGIA	"L" CLASS
FILTERING SURFACE	cmq	15.000
DUST CONTAINER	L	45



Lightweight and compact, the new MiniBull line meets all the cleaning requirements, even where an absolute filter is needed. MiniBull is a Wet & Dry singlephase unit, powerful and reliable, suitable for non continuous applications.

Fitted with *By-pass* motors, filter clogging and voltage warning lights indicators, independent *ON/OFF* switches and vertical manual shaker. It is among the most compact in its class. *MiniBull, great skills, for space saving.*



**SINGLEPHASE**

The modular system **Bull** has as its primary characteristics the **versatility**, a **robust** chassis with innovative design, a large filtering surface, a cyclonic inlet and a quick release system of the dust tank. Bull 1 is a compact single phase industrial vacuums, user friendly, robust and suitable to various applications. It is equipped with by-pass engines, clogged filter indicator, manual vertical filter shaker, vacuum gauge, power indicator and independent *ON/OFF* motors switches.



**BULL UNO 2 MOTORS**  
STANDARD "M" / +MTF / +HEPA14

POWER	Kw	2,4
MAX VACUUM	mBar	250
AIR FLOW	m³ / h	380
VOLTAGE	V	230
MOTORS	n° / Q.ty	2
FILTER MEDIA	IFA / BGIA	"M" CLASS
FILTERING SURFACE	cmq	24.000
DUST CONTAINER	L	65

**BULL UNO 3 MOTORS**  
STANDARD "M" / +MTF / +HEPA14 / +SP

POWER	Kw	3,9
VACUUM	mBar	250
AIR FLOW	m³ / h	540
VOLTAGE	V	230
MOTORS	n° / Q.ty	3
FILTER MEDIA	IFA / BGIA	"M" CLASS
FILTERING SURFACE	cmq	24.000
DUST CONTAINER	L	65

**BULL UNO UK**  
STANDARD "M" / +MTF / +HEPA14 / +SP

POWER	Kw	1,8
VACUUM	mBar	235
AIR FLOW	m³ / h	388
VOLTAGE	V	115
MOTORS	n° / Q.ty	2
FILTER MEDIA	IFA / BGIA	"M" CLASS
FILTERING SURFACE	cmq	24.000
DUST CONTAINER	L	65





**BULL 3/S**  
STANDARD "M" / +MTF  
SINGLEPHASE



POWER	kW	2,5
MAX VACUUM	mBar	230
AIR FLOW	m³ / h	320
VOLTAGE	V-HZ	230 - 50/60
INTAKE OPENING	mm	50/70
FILTER MEDIA	IFA / BGIA	"M" CLASS
FILTERING SURFACE	cmq	24.000
DUST CONTAINER	L	65
NOISE LEVEL	dBa	72

The modular system **Bull** has as its primary characteristics the versatility, a robust chassis with innovative design, a large filtering surface, a cyclonic inlet and a quick release system of the dust tank. The Bull is fitted as standard with a **singlephase** side channel turbine, relief valve, horizontal standard filter shaker, thermal switch and added silencers.

Series  
**BULL**

